

دستگاه چرخه گذاری دمایی

- مجهز به صفحه نمایش ۷ اینچ تاچ اسکرین رنگی جهت سهولت در اعمال تنظیمات
- قابلیت اتصال به کامپیوتر و نرم افزار مربوطه با قابلیت ذخیره سازی نتایج آزمون بر روی لاگر با قابلیت دسترسی از طریق پورت LAN و WiFi
- مجهز به سیستم کنترل دیجیتال با قابلیت ارسال اطلاعات دمایی به صورت وایرلس بر روی پنل اصلی دستگاه
- دارای ۲ مخزن جداگانه آب سرد و گرم با قابلیت تنظیم دما در محدوده مورد نظر با قابلیت ارسال اطلاعات دما
- دارای جریان حجمی مداوم و قابل تنظیم از ۱۰ تا ۴۰ لیتر در دقیقه
- مجهز به پمپ های طبقاتی استیل جهت ایجاد فشار با دقت ۰/۱ بار و حداکثر فشار ۱۵ بار
- مجهز به اینورتر جهت کنترل فشار پمپ با دقت بالا در محدوده مجاز
- دارای ۳ لاین خروجی با فشار یکسان با قابلیت اضافه کردن لاین
- دارای اسکلت با دسترسی مطلوب به محفظه آزمون از طریق درب های کشویی آلومینیومی
- محوطه تست قابل دسترسی از هر ۲ طرف به همراه ۴ درب آلومینیوم کشویی



Temperature Cycling

- Equipped with 7-inch color touch screen for easy setup
- Ability to connect to the computer and related software to save the test result on the logger and the ability to connect by LAN port and Wi-Fi
- Equipped with the digital control system and the ability of sending temperature information via wireless on the panel device
- Included with 2 separate compartment of warm and cold water to adjust temperature at the considered range and the ability of reporting temperature information
- Included with continuous volume flow that can be adjusted from 10 to 40 liters per minute
- Equipped with steel floor pumps to create pressure with an accuracy of 0.1 bar and a maximum pressure of 15 bar
- Equipped with an inverter to control the pump pressure with high accuracy within the allowed range
- Contained 3 output lines with the same pressure with the ability to add lines
- Included with a skeleton with optimal access to the test chamber through aluminum sliding doors
- Test area accessible from both sides with 4 sliding aluminum doors